

PCB LAYOUT  
TOP VIEW

SIM卡 Pin脚定义

8P	描述	No.	描述
P1	VCC	T1	DATA2
P2	RST	T2	CD/DAT3
P3	CLK	T3	CMD
--	Reserved	T4	VDD
P5	GND	T5	CLK
P6	VPP	T6	VSS
P7	I/O	T7	DAT0
--	Reserved	T8	DAT1

TF卡 Pin脚定义





TABLE A:

4	底座	1	STAINLESS STEEL
3	SHELL	1	STAINLESS STEEL/SOLDER TAIL GOLD PLATED
2	CONTACT	14	COPPER ALLOY/CONTACT AREA GOLD PLATED
1	HOUSING	1	HIGH TEMPERATURE UL 94-V0 BLACK
ITEM	NAME	QTY	MATERIAL / FINISH

CUSTOMER  
DRAWING

YTCONN  
http://www.hnytconn.com

Dongguan YTCONN  
Electronics Technology Co., Ltd

GENERAL TOLERANCE

DRAWING

DEV1

TITLE:

DOUBLE SIM CARD+TF CARD  
3IN1卡座 (铁壳前两脚SMT型)

ANGEL TOLERANCE

APPROVED

P/N:

SM63-20CB07-01

DATE

2016.09.18

DRAWING NO.

C-SM63-01

UNIT

mm

SCALE

1:1

SIZE

A4

SHEET

1 of 1

REV

A

料号编码

SM63-20 C B 07-01

① ② ③ ④ ⑤

① 产品系列:

SM63: (DOUBLE SIM CARD+TF CARD) 3IN1 卡座

② 产品PIN数:

20: 20PIN

③ 塑胶材料:

C: LCP

④ 塑胶颜色:

B: 黑色

⑤ 产品流水号

01: 铁壳前两脚SMT型

NOTES:

1. ELECTRICAL SPECIFICATIONS:

CURRENT RATING: 0.5A,

VOLTAGE RATING: 5V,

CONTACT RESISTANCE: 50 MILL.OHM MAX.

INSULATION RESISTANCE: 1000 MEG.OHM MIN.

2. MECHANICAL SPECIFICATIONS:

DURABILITY: 5000 CYCLES MIN.